



EUROPEAN PATENT APPLICATION

(43) Date of publication:
04.10.2001 Bulletin 2001/40

(51) Int Cl.7: A61F 13/512, A61F 13/534

(21) Application number: 01303148.9

(22) Date of filing: 02.04.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR

Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Onishi, Kazuaki, Technical Center
Mitoyo-gun, Kagawa-ken 769-1602 (JP)

(74) Representative: Parry, Christopher Stephen
Saunders & Dolleymore,
9 Rickmansworth Road
Watford, Herts. WD18 0JU (GB)

(30) Priority: 31.03.2000 JP 2000099022


(71) Applicant: UNICHARM CORPORATION
Kawanoe-shi, Ehime 799-01 (JP)

(54) **Body fluid absorbent sanitary article**

(57) A sanitary article 10 includes an absorbent structure composed of a liquid-pervious topsheet 11, a liquid-impervious backsheet 12 and a liquid-absorbent core 13 disposed therebetween, an absorbent upper panel 1 which is formed with a fibrous web and attached to an upper surface of the topsheet 11. The absorbent

upper panel 1 has a plurality of openings 2 extending through the panel 1 in its thickness direction and spaced one from another in a direction intersecting the thickness direction and a wall 3 defining each of the openings 2 wherein the wall 3 has a fiber density grade which is higher in an upper region of said wall and lower in a lower region of said wall lying adjacent the topsheet.

FIG.1



Description

[0001] This invention relates to body fluid absorbent sanitary article such as a disposable diaper, a sanitary napkin, a liquid-absorbent pad for an incontinent patient or the like.

[0002] Japanese Patent Application Publication No. 1999-318976A describes a disposable diaper comprising a liquid-pervious topsheet, a liquid-impervious backsheet and a liquid-absorbent core disposed between these two sheets, longitudinally configuring front and rear waist regions and a crotch region extending between these two waist regions, wherein the diaper is formed over its approximate rear half as viewed longitudinally thereof with a plurality of ridges made of absorbent material covered with a liquid-pervious sheet. The ridges transversely extend on the inner surface of the diaper and each pair of the adjacent ridges are longitudinally spaced apart from each other by a predetermined dimension. With such known diaper, the ridges serve as barriers to restrict or prevent excretion from flowing forwardly of the diaper and at the same time to prevent excretion from leaking rearwardly of the diaper.

[0003] The Publication describes that the preventive effect for rearward leakage of excretion can be significantly improved since the absorbent material of the ridges is able to absorb moisture contained in excretion. However, it is impossible for the absorbent material of the ridges to absorb solid substances contained in excretion of high viscosity such as loose passage or liquid feces. Consequently, such solid components may stay on the outer surface of the topsheet exposed between each pair of the adjacent ridges or on the outer surface of the liquid-pervious sheet covering the ridges and these solid components may stick to a wearer's skin.

[0004] It is an object of this invention is to provide a body fluid absorbent sanitary article adapted to minimize an anxiety that excretion of high viscosity such as loose passage, liquid feces or menstrual discharge might stick to a wearer's skin.

[0005] According to this invention, there is provided a body fluid absorbent sanitary article comprising an absorbent structure which includes an absorbent core and an absorbent upper panel which is formed with a fibrous web having a compressive recovery elasticity and attached to an upper surface of the absorbent structure, the absorbent upper panel having a plurality of openings extending through the absorbent upper panel in a thickness direction thereof and spaced one from another in a direction intersecting the thickness direction and a wall defining each of the openings wherein the wall has a fiber density grade which is higher in an upper region of the wall and lower in a lower region of the wall lying adjacent an upper surface of the absorbent structure.

[0006] The body fluid absorbent sanitary article according to this invention enables high viscosity excretion such as loose passage, liquid feces and menstrual discharge to flow into the openings of the absorbent upper

panel without permeating into the high density fibrous layer of the wall. Within the openings, most of a moisture content of the high viscosity excretion permeates through the topsheet into the absorbent structure and partially permeates into the low density fibrous layer. The portion of the moisture content having permeated into the low density fibrous layer moves from the low density fibrous layer toward the upper surface of the absorbent structure and permeates through the upper surface into the absorbent structure. Within the openings, a solid content of the high viscosity excretion permeates into the low density fibrous layer. In this manner, there is no anxiety that the high viscosity excretion might stay on the top surface of the panel. In other words, the high viscosity excretion is normally spaced apart from the wearer's skin and a possibility that the high viscosity excretion may stick to the wearer's skin can be minimized. Even if the panel is collapsed under the wearer's body weight, the high viscosity excretion is prevented by the high density fibrous layer of the wall from flowing back to the top surface of the panel.

[0007] Urine is absorbed by the high density fibrous layer of the wall and gradually permeates from the high density fibrous layer into the low density fibrous layer. Then, urine flows from the low density fibrous layer toward the upper surface of the absorbent structure and permeates through the upper surface into the structure. Within the openings, most of urine permeates through the upper surface into the structure and partially permeates into the low density fibrous layer. The portion of urine having permeated into the low density fibrous layer flows from the low density fibrous layer toward the upper surface of the absorbent structure and permeates through the upper surface into the structure.

[0008] Fig. 1 is a perspective view depicting a partially cutaway diaper as one embodiment of this invention;

[0009] Fig. 2 is a sectional view taken along line A - A in Fig. 1;

[0010] Fig. 3 is a fragmentary sectional view of an absorbent panel and a topsheet schematically illustrating a flow of loose passage; and

[0011] Fig. 4 is a view similar to Fig. 3 schematically illustrating a flow of urine.

[0012] Details of a disposable diaper as an example of a body fluid absorbent sanitary article according to this invention will be more fully understood from the description given hereunder with reference to the accompanying drawings.

[0013] Fig. 1 is a perspective view depicting a partially cutaway diaper 10 and Fig. 2 is a sectional view taken along line A - A in Fig. 1. The diaper 10 comprises an absorbent structure including a liquid-pervious topsheet 11 made of a hydrophilic nonwoven fabric, a liquid-impervious backsheet 12 and a liquid-absorbent core 13 disposed between these two topsheet 11 and the backsheet 12 and joined to at least one of these two sheets 11, 12. The diaper 10 configurationally comprises a front waist region 19 (first region), a rear waist region 21 (sec-

ond region) and a crotch region 20 (intermediate region) extending between these front and rear waist regions 19, 21. The diaper 10 is contoured by transversely opposite side edges 10a longitudinally extending parallel to each other and curving inwardly of the diaper 10 so as to describe circular arcs in the crotch region 20 and longitudinally opposite ends 10b transversely extending parallel to each other.

[0014] The diaper 10 is provided along the transversely opposite side edges 10a with longitudinally extending thread-like elastic members 15 joined under tension thereto to be associated with leg-openings. The diaper 10 is further provided along the longitudinally opposite ends 10b with transversely extending elastic members 16 disposed between the topsheet 11 and the backsheet 12 and joined under tension to at least one of these sheets 11, 12 to be associated with a waist-opening. The diaper 10 is provided immediately outside transversely opposite side edges 13a with a pair of liquid-barrier cuffs 14 being spaced apart from each other and longitudinally extending parallel to each other.

[0015] A rectangular mat-like absorbent upper panel 1 is attached to the outer surface of the topsheet 11 so that its longer sides may be oriented longitudinally of the diaper 10. The absorbent upper panel 1 lies above a zone of the core 13 defined between the respective cuffs 14 so as to extend across the rear waist region 21 and the crotch region 20 of the diaper 10 and has its bottom surface joined to the outer surface of the topsheet 11 with an adhesive agent or heat-sealing.

[0016] The absorbent upper panel 1 is made of a fibrous web which is elastically recoverable from compressed state and has a plurality of square openings 2 extending through the absorbent upper panel in its thickness direction and a frame-like wall 3 defining the respective openings 2.

[0017] The openings 2 are spaced one from another obliquely of the transversely opposite side edges 10a as well as the longitudinally opposite ends 10b. The wall 3 comprises a plurality of first ribs 3A and a plurality of second ribs 3B. The first ribs 3A extend between each pair of the adjacent openings 2 and are spaced one from another obliquely of the transversely opposite side edges 10a as well as the longitudinally opposite ends 10b of the diaper 10. Arrangement of the second ribs 3B is similar to the arrangement of the first ribs 3A except that they are spaced one from another in the oblique direction which is orthogonal to the first ribs 3A.

[0018] Each of the openings 2 formed in the absorbent upper panel 1 is defined by a pair of the adjacent first ribs 3A and a pair of the adjacent second ribs 3B intersecting the pair of the adjacent first ribs 3A. Each of the ribs 3A, 3B has a low density fibrous layer 3a overlying the outer surface of the topsheet 11 and a high density fibrous layer 3b overlying the low density fibrous layer 3a. The layer 3a has a fiber density lower than a fiber density of the layer 3b as well as a fiber density of the topsheet 11.

[0019] The diaper 10 is provided on the transversely opposite side edges 10a in the rear waist region 21 with respective proximal ends of tape fasteners 18 so that these tape fasteners 18 may extend transversely inward. In the front waist region 19, a rectangular target tape strip (not shown) is attached to the outer surface of the backsheet 12 so that the tape fastener 18 may be anchored on this target tape strip.

[0020] The barrier cuffs 14 lie immediately outside the transversely opposite side edges 13a of the core 13 and each of these barrier cuffs 14 has a fixed side edge portion 14a fixed to the outer surface of the topsheet 11 and extending longitudinally of the diaper 10, a free side edge portion 14b lying in the crotch region 20 and extending inward transversely of the diaper 10 under a biasing effect tending to raise the free side edge portion 14b on the diaper 10, and longitudinally opposite fixed ends 14c collapsed inward transversely of the diaper 10 and fixed, in such state, to the outer surface of the topsheet 11 in the front and rear waist regions 19, 21, respectively. A longitudinally extending elastic member 17 is joined under tension to the free side edge portion 14b of the cuff 14 so that a portion of the free side edge portion 14b may covers the elastic member 17.

[0021] Referring to Fig. 1, the diaper 10 longitudinally curves with its inner surface inside and the elastic members 15, 16, 17 relieved of tension to form gathers along the transversely opposite side edges 10a as well as the longitudinally opposite ends 10b and the respective free side edge portions 14b of the cuffs 14. In this state of the diaper 10, the topsheet 11 cooperates with the cuffs 14 to form a pair of pockets P opening inward transversely of the diaper 10.

[0022] The tape fasteners 18 have their inner surfaces coated on their free ends with a pressure-sensitive adhesive agent and may be anchored on the target tape strip with the pressure-sensitive adhesive agent to form the waist-opening and the leg-openings (not shown) of the diaper 10.

[0023] Transversely opposite side edges 11a of the topsheet 11 extend laterally outward slightly beyond the transversely opposite side edges 13a of the core 13 and the transversely opposite side edges 12a of the backsheet 12 as well as transversely outer edges of the respective cuffs 14 extend further beyond the transversely opposite side edges 11a of the topsheet 11. The transversely opposite side edges 11a of the topsheet 11 are disposed between the transversely opposite side edges 12a of the backsheet 12 and the transversely outer side edges 14d of the respective cuffs 14 and are joined to at least one the backsheet 12 and the cuffs 14. The transversely opposite side edges 12a of the backsheet 12 and the transversely outer side edges 14d of the respective cuffs 14 are placed upon and joined to each other. The elastic members 15 associated with the legs are disposed between the transversely opposite side edges 12a of the backsheet 12 and the transversely opposite side edges 14d and are attached to at least one

of these side edges 12a, 14d. In the vicinity of the longitudinally opposite ends 10b of the diaper 10, respective portions of the topsheet 11, the backsheet 12 and the cuffs 14 extending longitudinally outward from longitudinally opposite ends 13b of the core 13 are placed upon and joined to one another.

[0024] Fig. 3 is a fragmentary sectional view of the panel 1 and the topsheet 11 schematically illustrating a flow of loose passage and Fig. 4 is a view similar to Fig. 3 schematically illustrating a flow of urine, in which an arrow X indicates flow of loose passage and an arrow Y indicates flow of urine. As will be apparent from Fig. 3, it is difficult for loose passage discharged onto the frame-like wall 3 to permeate into a high density fibrous layer 3b due to a relatively high viscosity and such loose passage tends to stay on a top surface of the frame-like barrier 3. However, loose passage gradually flows from the top surface into the openings 2 as the wearer's skin and the top surface of the wall 3 repeatedly rub against each other, as indicated by the arrow X. Within the openings 2, moisture content of loose passage permeates into the topsheet 11 and is absorbed by the core 13 while solid content of loose passage still staying within the openings permeates together with a portion of the moisture content into a low density fibrous layer 3a. The fibrous layer 3a has a fibrous density lower than that of the fibrous layer 3b and fibrous interstices sufficiently wider than those of the fibrous layer 3b to facilitate even the solid content of loose passage to permeate into the fibrous layer 3a. The moisture content of loose passage having permeated into the low density fibrous layer 3a then flows from this low density fibrous layer 3a toward the topsheet 11 and permeates through the topsheet 11 into the core 13. The moisture content is absorbed by the core 13 and the solid content permeates into the low density fibrous layer 3a. In this manner, loose passage is reliably spaced apart from the wearer's skin.

[0025] As illustrated in Fig. 4, urine discharged onto the panel 1, specifically onto the top surface of the wall 3 permeates into the high density fibrous layer 3b, spreads therein and then gradually permeates from the high density fibrous layer 3b into the low density fibrous layer 3a. urine discharged into the openings 2 reaches the topsheet 11 and permeates this into the core 13. In the course of permeating through the topsheet 11, a portion of use still staying within the openings 2 permeates through the low density fibrous layer 3a of the wall 3 to the topsheet 11 and permeates through the topsheet 11 into the core 13.

[0026] A capillary effect in the topsheet 11 is higher than that in the low density fibrous layer 3a since the topsheet 11 has a fibrous density higher than that of the low density fibrous layer 3a. Such capillary effect in the topsheet 11 cooperates with an absorbency of the core 13 to guide the moisture content of loose passage and urine from the low density fibrous layer 3a toward the topsheet 11.

[0027] The barrier 3 of the absorbent upper panel 1

has a thickness L of 2 - 30 mm. The thickness L smaller than 2 mm would decrease a receiving capacity of the low density fibrous layer 3a of the panel 1 for loose passage so that the low density fibrous layer 3a could not the entire solid content of loose passage. The thickness L more than larger than 30 mm would make the wall 3 of the panel 1 bulky so that the wearer might experience a feeling of discomfort when the diaper 10 is put on the wearer's body.

[0028] Of the wall 3, the low density fibrous layer 3a has a fiber basis weight of 30 - 45 g/m² and a fiber density of 0.01 - 0.03 g/cm³, and the high density fibrous layer 3b has a fiber basis weight of 45 - 300 g/m² and the high density fibrous layer 3b has a fiber density of 0.03 - 0.10 g/cm³.

[0029] If the low density fibrous layer 3a has a fiber basis weight less than 30 g/m² and a fiber density less than 0.01 g/cm³, a strength of the wall 3 will be decreased so that the barrier 3 may be easily collapsed under the wearer's body weight and loose passage may flow back from the low density fibrous layer 3a. If the low density fibrous layer 3a has a fiber basis weight exceeding 45 g/m² and a fiber density exceeding 0.03 g/cm³, the fibrous interstices of the low density fibrous layer 3a will become dense and obstruct the solid content of loose passage from smoothly permeating into the low density fibrous layer 3a.

[0030] If the high density fibrous layer 3b has a fiber basis weight less than 45 g/m² and a fiber density of 0.03 g/cm³, the fibrous interstices will become too coarse to prevent the solid content of loose passage from permeating into the high density fibrous layer 3b. With the solid content having permeated into the high density fibrous layer 3b, the solid content may turn back from the high density fibrous layer 3b to the top surface of the panel 1 as the wall 3 is compressed under the wearer's body weight. If the high density fibrous layer 3b has a fiber basis weight exceeding 300g/m² and a fiber density exceeding 0.10 g/cm³, a stiffness of the high density fibrous layer 3b will be increased and the high density fibrous layer 3b may uncomfortably stimulate the wearer's skin.

[0031] In the wall 3, the low density fibrous layer 3a has a fiber fineness of 2.2 - 6.5 dtex and the high density fibrous layer 3b has a fiber fineness of 0.5 - 2.2 dtex. The relatively high fiber fineness of the high density fibrous layer 3b enables this fibrous layer 3b to have the correspondingly dense fiber interstices.

[0032] Each of the openings 2 has an opening area of 10 - 1600 mm² and its occupancy ratio per unit area of the panel 1 is 20 - 80 %. If the opening area is less than 10 mm² and the occupancy ratio is less than 20 %, a receiving capacity of the openings for loose passage will be decreased and it will be impossible for the solid content of loose passage to be rapidly guided from the openings 2 into the low density fibrous layer 3a. Consequently, loose passage may stay on the top surface of the panel 1. If the opening area exceeds 1600 mm² and

the occupancy ratio exceeds 80 %, a strength of the barrier 3 will be decreased and the barrier 3 may be easily collapsed under the wearer's body weight.

[0033] The panel 1 has a compressive modulus represented by an equation of $(a \text{ thickness under a load of } 35 \text{ g/cm}^2) \div (a \text{ thickness under a load of } 2 \text{ g/cm}^2) \times 100 = 20 - 80 \%$. With the compressive modulus less than 20 %, the wall 3 having been collapsed under the wearer's body weight would be unable to recover its initial state, resulting in a decreased receiving capacity of the low density fibrous layer 3a for loose passage, and it would be apprehended that loose passage might turn back from the low density fibrous layer 3a into which the loose passage has permeated. With the compressive modulus exceeding 80%, on the contrary, a stiffness of the wall 3 will increase and uncomfortably stimulate the wearer's skin.

[0034] It is possible to coat the top surface of the wall 3 with suitable water repellent. Coating with the water repellent ensures that an amount of excretion having permeated from the openings into the low density fibrous layer 3a and the high density fibrous layer 3b is reliably prevented from exuding back to the top surface of the wall 3. While the panel 1 is illustrated to extend across the rear waist region 21 and the crotch region 20, it is possible for the panel 1 to extend also into the front waist region 20.

[0035] An example of the absorbent panel 1 is made by a process comprising steps of discharging and dispersing short fibers of thermoplastic synthetic resin in air, accumulating these short fibers on a moving conveyor provided with a plurality of pins shaped in conformity of the openings so as to form a fibrous web, and subjecting the fibrous web on the moving conveyor to hot blast so that the short fibers may be fused together.

[0036] Another example of the panel 1 is made by a process comprising the steps of discharging molten thermoplastic synthetic resin from spinning nozzle, blasting air streams from gas spouts blast provided on both sides of the nozzle lip so that the molten synthetic resin may be spun by the air streams into superfine fibers, and collecting these spun fibers on a meshy moving conveyor. On the conveyor, the fibers are entangled and fused together by heat of the fibers themselves to form a fibrous web. Subsequently, the fibrous web is compressed by pressure rollers before or after cooled so that the fibrous web may be compression molded in a substantially uniform thickness.

[0037] The fiber used to form the panel 1 may be selected from a group including polyolefine-based fiber such as polypropylene or polyethylene fiber, polyester-based fiber such as polyethylene terephthalate polybutylene terephthalate, polyamide-based fiber such as nylon 66 or nylon 6, acryl-based fiber, cellulose-based fiber such as pulp, rayon or acetate, and superabsorption polymer fiber. It is also possible to disperse superabsorption polymer particles in fiber interstices of the fibrous web so that these polymer grains may be held

therein. The openings 2 are not limited to the square shaped openings as illustrated but may be also provided in the other shape such as a circular, oval rectangular or triangular shape.

[0038] The structure of the panel 1 is not limited to the combination of the low density fibrous layer 3a and the high density fibrous layer 3b. It is also possible to adjust the fiber density of the wall 3 to increase continuously or discontinuously from the vicinity of the topsheet 11 toward the top surface. In the panel 1 of such alternative arrangement, the wall 3 preferably has a fiber basis weight of 30 - 300 g/m² and a fiber density of 0.01 - 0.1 g/cm³. The fiber density of the barrier 3 in the vicinity of the topsheet 11 is preferably lower than that of the topsheet 11.

[0039] The backsheet 12 and the cuffs 14 may be formed with a hydrophobic nonwoven fabric, a liquid-impermeable plastic film or a laminated sheet consisting of hydrophobic nonwoven fabric and a plastic film, preferably by a breathable but liquid-impermeable sheet. It is also possible to use, as the stock material for the backsheet 12 and the cuffs 14, a composite nonwoven fabric (SMS nonwoven fabric) comprising a melt blown nonwoven fabric having a high water-resistance of which the opposite sheet surfaces are sandwiched between sheet surfaces of a melt blown nonwoven fabric having a high strength and a high flexibility.

[0040] The nonwoven fabric may be selected from a group including a spun lace nonwoven fabric, a needle punch nonwoven fabric, a melt blown nonwoven fabric, a thermal bond nonwoven fabric, a spun bond nonwoven fabric and a chemical bond nonwoven fabric.

[0041] The component fiber of the nonwoven fabric may be selected from a group including polyolefine, polyester and polyamide fibers and conjugated fiber of polyethylene/polypropylene or polyester.

[0042] The core 13 may be formed with a mixture of fluff pulp and high absorption polymer particles compressed to a desired thickness and then entirely covered with a water-pervious sheet (not shown) such as tissue paper.

[0043] Joining of the core 13 to the sheets 11, 12, bonding of the sheets 11, 12 as well as the barrier cuffs 14 and attachment of the elastic members 15, 16, 17 may be carried out using a suitable adhesive agent such as a hot melt adhesive agent or a pressure-sensitive adhesive agent or a heat-sealing technique.

[0044] This invention is applicable not only to the disposable diaper 10 but also to a sanitary napkin or a liquid-absorbent pad for incontinent patient or the like.

Claims

1. A body fluid absorbent sanitary article comprising an absorbent structure which include an absorbent core and an absorbent upper panel which is formed with a fibrous web having a compressive recovery

elasticity and attached to an upper surface of said absorbent structure, said absorbent upper panel having a plurality of openings extending through said absorbent upper panel in a thickness direction thereof and spaced one from another in a direction intersecting said thickness direction and a wall defining each of said openings wherein said wall has a fiber density grade which is higher in an upper region of said wall and lower in a lower region of said wall lying adjacent an upper surface of said absorbent structure.

2. The sanitary article according to Claim 1, wherein the upper surface of said absorbent structure has a fiber density higher than that in the lower region of said wall.
3. The sanitary article according to Claim 1, wherein said wall comprises a low density fibrous layer lying in vicinity of the upper surface of said absorbent structure and a high density fibrous layer overlying said low density fibrous layer.
4. The sanitary article according to Claim 1, wherein said wall has a thickness of 2 - 30 mm.
5. The sanitary article according to Claim 1, wherein most of fibers forming said low density fibrous layer has a fineness of 2.2 - 6.5 dtex and most of fibers forming said high density fibrous layer has a fineness of 0.5 - 2.2 dtex.
6. The sanitary article according to Claim 1, wherein each of said openings has an opening area of 10 - 1600 mm² and an occupancy ratio of 20 - 80 % per unit area of said panel.
7. The sanitary article according to Claim 1, wherein said absorbent upper panel has a compressive modulus represented by an equation of (a thickness under a load of 35 g/cm²) ÷ (a thickness under a load of 2 g/cm²) X 100 = 20 - 80 %.
8. The sanitary article according to Claim 1, wherein said absorbent structure comprises a liquid-pervious topsheet, a liquid-impervious backsheet and a liquid-absorbent core disposed therebetween to define a first region, a second region and an intermediate region extending said first and second regions, and said absorbent upper panel being put on an upper surface of said topsheet.
9. The sanitary article according to Claim 1, wherein said topsheet is made of a hydrophilic nonwoven fabric and defines the upper surface of said absorbent structure.

FIG.1




FIG. 2




FIG.3





FIG.4



THIS PAGE BLANK (USPTO)



EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
30.01.2002 Bulletin 2002/05

(51) Int Cl.7: A61F 13/512, A61F 13/534

(43) Date of publication A2:
04.10.2001 Bulletin 2001/40

(21) Application number: 01303148.9

(22) Date of filing: 02.04.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(71) Applicant: UNICHARM CORPORATION
Kawanoe-shi, Ehime 799-01 (JP)

(72) Inventor: Onishi, Kazuaki, Technical Center
Mitoyo-gun, Kagawa-ken 769-1602 (JP)

(30) Priority: 31.03.2000 JP 2000099022


(74) Representative: Parry, Christopher Stephen
Saunders & Dolleymore, 9 Rickmansworth Road
Watford, Herts. WD18 0JU (GB)

(54) Body fluid absorbent sanitary article

(57) A sanitary article 10 includes an absorbent structure composed of a liquid-pervious topsheet 11, a liquid-impervious backsheet 12 and a liquid-absorbent core 13 disposed therebetween, an absorbent upper panel 1 which is formed with a fibrous web and attached to an upper surface of the topsheet 11. The absorbent

upper panel 1 has a plurality of openings 2 extending through the panel 1 in its thickness direction and spaced one from another in a direction intersecting the thickness direction and a wall 3 defining each of the openings 2 wherein the wall 3 has a fiber density grade which is higher in an upper region of said wall and lower in a lower region of said wall lying adjacent the topsheet.

FIG. 1





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 30 3148

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.CI.7)
X	US 5 817 394 A (ALIKHAN MIR INAYETH ET AL) 6 October 1998 (1998-10-06) * column 5, line 15-63 * * column 6, line 29-44 * * column 8, line 36-61 * * column 11, line 58-62 * * column 19, line 7-17; figures 1,2,4-6 *	1-9	A61F13/512 A61F13/534
X	US 4 780 352 A (PALUMBO GIANFRANCO) 25 October 1988 (1988-10-25) * column 5, line 50 - column 6, line 18; figures 1,4,5 *	1-4,6,7	
X	EP 0 815 819 A (UNI CHARM CORP) 7 January 1998 (1998-01-07) * claims; figures *	1-6	
A	US 5 986 167 A (MYERS NANCY JO ET AL) 16 November 1999 (1999-11-16) * column 4, line 64 - column 5, line 23 * * column 7, line 26-42 * * column 10, line 31-60; figures 1-3,6 *	1-4,6	
A	EP 0 953 324 A (PROCTER & GAMBLE) 3 November 1999 (1999-11-03) * abstract * * column 12, line 28-45; figures 1-4 *	1,6,8,9	TECHNICAL FIELDS SEARCHED (Int.CI.7) A61F
A	EP 0 758 543 A (UNI CHARM CORP) 19 February 1997 (1997-02-19) * column 3, line 5 - column 4, line 3; figures *	1-3	
A	US 4 276 338 A (FORRY MARK E ET AL) 30 June 1981 (1981-06-30) * claims; figures *	1-3	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 6 December 2001	Examiner Seabra, L
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document</p> <p>T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons &: member of the same patent family, corresponding document</p>			

EPO FORM 1503 (03.02.04) (P04C01)

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 01 30 3148

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

06-12-2001

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5817394	A	06-10-1998	AU 5595394 A	08-06-1994
			CN 1119581 A	03-04-1996
			DE 69330181 D1	31-05-2001
			DE 69330181 T2	23-08-2001
			EP 0667814 A1	23-08-1995
			JP 8504136 T	07-05-1996
			MX 9306964 A1	31-01-1995
US 4780352	A	25-10-1988	IT 1182491 B	05-10-1987
			AT 53485 T	15-06-1990
			AU 588607 B2	21-09-1989
			AU 5943786 A	08-01-1987
			BR 8603291 A	24-02-1987
			CA 1273188 A1	28-08-1990
			DE 3671837 D1	19-07-1990
			EP 0207904 A1	07-01-1987
			ES 2002097 A6	16-07-1988
			GR 861713 A1	04-11-1986
			JP 1963246 C	25-08-1995
			JP 6091894 B	16-11-1994
			JP 62038157 A	19-02-1987
			MX 163503 B	25-05-1992
			PT 8522 U	29-01-1993
			PT 82911 A	01-08-1986
EP 0815819	A	07-01-1998	JP 10014979 A	20-01-1998
			AU 714743 B2	13-01-2000
			AU 2620797 A	15-01-1998
			CN 1175395 A	11-03-1998
			EP 0815819 A2	07-01-1998
			US 5885267 A	23-03-1999
US 5986167	A	16-11-1999	US 5925026 A	20-07-1999
EP 0953324	A	03-11-1999	EP 0953324 A1	03-11-1999
			AU 3666599 A	16-11-1999
			EP 1076541 A1	21-02-2001
			WO 9955273 A1	04-11-1999
EP 0758543	A	19-02-1997	JP 3208289 B2	10-09-2001
			JP 9051913 A	25-02-1997
			AU 723448 B2	24-08-2000
			AU 6085296 A	20-02-1997
			CA 2182634 A1	16-02-1997
			DE 69612594 D1	31-05-2001
			DE 69612594 T2	11-10-2001

EPO FORM P0457

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 3148

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

06-12-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0758543 A		EP 0758543 A1	19-02-1997
		KR 158549 B1	15-12-1998
		US 5846231 A	08-12-1998
US 4276338 A	30-06-1981	CA 1150488 A1	26-07-1983
		JP 56009459 A	30-01-1981

EPO FORM P459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82